

Light Truck Tires Technical Planning Sheet

Representative planning sheet - not final certified technical data.

GLOBAL TIRE EXPORT COMPANY LIMITED | salesmanager@globaltireexport.com

Category: Light Truck Tires

Use: Reinforced LT tires for pickups, service vehicles, commercial vans and work fleets serv

Certification note: Certification availability is SKU- and market-specific. DOT, ECE, GCC, S

Data fields: Tire Size | Load Range | Ply Rating | Typical Speed | Pattern Class | Primary A

LT265/70R17 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /
LT245/75R16 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Wor
LT285/55R20 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Wor
LT235/85R16 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /
LT275/65R18 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Wor
LT315/70R17 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Wor
LT265/65R17 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /
LT275/70R18 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Wor
LT255/75R17 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Uti
LT225/75R16 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /
LT285/75R16 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Uti
LT305/70R16 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Uti
LT245/70R17 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /
LT265/75R16 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Uti
LT285/60R20 | E typical | 10 PR typical | S / T pattern-specific | A/T option | Pickup / Uti
LT275/55R20 | E typical | 10 PR typical | S / T pattern-specific | Highway / A/T | Pickup /

Final load, speed, inflation, dimensions, certification, labels and sidewall markings must b