

Semi Truck Tires Technical Planning Sheet

Representative planning sheet - not final certified technical data.

GLOBAL TIRE EXPORT COMPANY LIMITED | salesmanager@globaltireexport.com

Category: Semi Truck Tires

Use: Factory-direct steer, drive, trailer and all-position truck tires for US fleets, distri

Certification note: Certification availability is SKU- and market-specific. DOT, ECE, GCC, S

Data fields: Tire Size | Position | Load Range | Ply Rating | Typical Tread | Planning Load

295/75R22.5 | Steer / Trailer | G / H | 14 / 16 PR | 18-20/32 in | Confirm by pattern | DOT
11R22.5 | Steer / Drive / Trailer | H | 16 PR | 18-30/32 in | Confirm by pattern | DOT / ECE
11R24.5 | Steer / Drive / Trailer | H | 16 PR | 18-30/32 in | Confirm by pattern | DOT / ECE
315/80R22.5 | All-position / Drive | L | 20 PR | 20-30/32 in | Confirm by pattern | ECE / ex
285/75R24.5 | Steer / Trailer | G / H | 14 / 16 PR | 18-20/32 in | Confirm by pattern | DOT
275/80R22.5 | All-position | H | 16 PR | 18-22/32 in | Confirm by pattern | Market-specific
255/70R22.5 | All-position | H | 16 PR | 16-18/32 in | Confirm by pattern | Market-specific
245/70R19.5 | Steer / Trailer | H | 16 PR | 15-18/32 in | Confirm by pattern | DOT / ECE pro
12R22.5 | All-position / Drive | H / J | 16 / 18 PR | 20-30/32 in | Confirm by pattern | ECE
10R22.5 | All-position | G / H | 14 / 16 PR | 18-22/32 in | Confirm by pattern | Market-spec
9R22.5 | All-position | G / H | 14 / 16 PR | 17-20/32 in | Confirm by pattern | Market-speci
8.25R20 | All-position | H | 16 PR | 16-20/32 in | Confirm by pattern | GCC / SASO option
11R20 | All-position / Drive | H | 16 PR | 18-28/32 in | Confirm by pattern | GCC / SASO opt
10R20 | All-position / Drive | H | 16 PR | 18-26/32 in | Confirm by pattern | GCC / SASO opt
315/70R22.5 | Steer / Drive | L | 20 PR | 20-28/32 in | Confirm by pattern | ECE / export pr
385/65R22.5 | Trailer / All-position | J / K | 18 / 20 PR | 18-22/32 in | Confirm by pattern

Final load, speed, inflation, dimensions, certification, labels and sidewall markings must b